

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number  
**WO 2005/094528 A2**

(51) International Patent Classification: Not classified

(21) International Application Number:  
PCT/US2005/009857

(22) International Filing Date: 24 March 2005 (24.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/556,278 25 March 2004 (25.03.2004) US

(71) Applicant (for all designated States except US): TIMKEN  
US CORPORATION [US/US]; 59 Field Street, Torrington,  
CT 06790 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): AI, Xiaolan

[US/US]; 4480 Noble Loon Street NW, Massillon, OH  
44646 (US). DEGRANGE, David, A. [US/US]; 8238  
Grayson Green NW, Massillon, OH 44646 (US).


(74) Agent: SMITH, David, B.; Michael Best & Friedrich,  
LLP, 100 East Wisconsin Avenue, Milwaukee, WI 53202  
(US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: STEERING WHEEL MOUNTING ASSEMBLY



(57) Abstract: A steering wheel mounting assembly comprising first and second stationary rings, the second stationary ring being adapted for connection to a vehicle frame. The assembly further comprises a steering hub having a spindle with a radial flange extending therefrom. The spindle is adapted for connection with a steering shaft and the radial flange is adapted for connection with a steering wheel. The spindle has a first bearing raceway for engaging a bearing of the first stationary ring and a second bearing raceway for engaging a bearing of the second stationary ring. The steering hub has at least one opening that defines a bearing surface. A friction roller assembly, having a shaft with a third bearing thereabout, is positioned in the opening such that as the third bearing rotates relative to the bearing surface, the third bearing moves radially outward and the shaft engages the first and second cylindrical raceways.

WO 2005/094528 A2



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— without international search report and to be republished upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*